

REPLAY 55 EVO A

The Replay EVO range includes a series of basic chamber wrapping machines, while not sacrificing the typical quality of the products by Record Packaging. Thanks to the excellent value for money, offering new cutting-edge systems at affordable prices, it is the most competitive proposition among all our series of chamber machines.

Technical Solutions

- Option of having an 'Automatic' work cycle (press the start button cycles performed in sequence, interrupted by the programmed pause interval) and a 'Manual' work cycle (press the start button to perform one packaging cycle)
- Automatic lid opening
- Frontal control interface: intuitive programming
- Innovative upper hood fixing, easier maintenance
- Safety control on sealing blades: safer machine
- Roll support with bigger diameter (250 mm)
- Packaging plate independent from roll support: suitable for the packaging of small products with the same film roll
- Innovative micro puncher: continuous and accurate perforation
- Double display: 2 digit for programs and settings and 4 digit as pieces counter
- 6 programs digital control panel easy to be used
- Counter pieces included: more complete equipment
- Power board access with frontal door
- Higher screened plate: more protection of the heating elements
- More powerful fan motor: superior shrinking performance
- Extra safety thermostat on the heating elements: safer machine
- New rubber support without glue



Technical Features

Electrical power supply	200V 50/60Hz 3Ph 400V 50/60Hz 3Ph 230V 50/60Hz 1Ph
Maximum power installed	4,0 kW (200V) 4,1 kW (400V 50Hz) 4,4 kW (400V 60Hz) 3,4 kW (230V 1Ph)
Maximum current	18 A (200V) 10,5 A (400V 50Hz) 11 A (400V 60Hz) 15 A (230V 1Ph)
Hourly production	0-550
Useful dimensions of sealing bars	540x390 mm
Maximum reel dimensions (Ø x length)	Ø250x600 mm
Maximum product dimensions Work surface height	500x380x200 mm 925 mm
Machine dimensions (open hood)	1260x810x1310 mm
Machine dimensions (closed hood)	1260x810x1165 mm
Machine weight (net / gross) Machine color	133/154 kg RAL7035 peeled
Packaging flat color	RAL7016 peeled

Layout Drawing

