

# REPLAY 85 EVO

The Replay EVO range includes a series of basic chamber wrapping machines, while not sacrificing the typical quality of the products by Record Packaging. Thanks to the excellent value for money, offering new cutting-edge systems at affordable prices, it is the most competitive proposition among all our series of chamber machines.

## Technical Solutions

- Innovative upper hood fastening: simplified maintenance and enhanced stability
- Sealing blades safety control: enhanced machine safety
- Support with larger reel diameter (300 mm): suitable for micro-punched film to pack bread
- Packaging plate separated from the reel support: suitable to package even very small products with the same film reel.
- Innovative micro-perforator: continuous and optimal perforation
- New ultra-flat tactile membrane: waterproof and with intuitive graphics not associated with the board 3-digit display: visibility and comprehensive information.
- Board with 10 programs to meet any programming need.
- Piece counter included: a more exhaustive supply of equipment
- Board access through a door: easier maintenance from the front
- Longer screened plate: chamber opening flap protection
- Boosted fan motor: superior shrinking performance
- Added safety thermostat installed directly on the resistor of the heat chamber: greater safety for the machine.
- Glue-less neoprene rubber support: easy to replace, does not require the use of glue.



## Technical Features

Electrical power supply	200V 50/60Hz 3Ph 208V 60Hz 3Ph 400V 50/60Hz 3Ph
MAX power installed	5,5 kW (200V) 6,6 kW (208V) 6,0 kW (400V)
Maximum current	"21 A (200V) 20 A (208V) 9,5 A (400V)"
Hourly output	0-300
Available dimensions of the sealing bars	840x590 mm
Maximum reel dimensions (Ø x length)	Ø300x800 mm
MAX product size	800x500x200 mm
Work surface height	940 mm
Machine dimensions (open hood)	1950x1000x1480 mm
Machine dimensions (closed hood)	1950x1000x1180 mm
Machine weight (Net/Gross)	212/264 kg

## Layout Drawing

