

MVS50 X

Reliable and User-Friendly Chamber Vacuum Sealer with Carriage

The MVS X series by minipack®-torre introduces a line of chamber vacuum sealers characterized by high-quality technology and functionality, coupled with the exceptional user-friendliness inherent in the company's products. A notable feature is the seamless integration of new and specific functions into these machines, a result of collaboration with esteemed chefs and industry professionals, ensuring optimal compatibility with the requirements of food vacuum packaging. Protected against infiltration by a tactile touch keyboard hermetically affixed to the front body, these machines boast a control display facilitating the configuration of up to 10 distinct customized programs tailored to the diverse needs of the food industry's vacuum packaging.

Additionally, these chamber vacuum sealers incorporate a special sensor to monitor the vacuum level within the chamber. A prompt alerts users to the necessity of an oil change when required. Another noteworthy feature is the ability to calibrate the packaging machine based on the operational altitude, ensuring adaptation to the atmospheric pressure of the location.



Technical Features

Parameter	Specification
Electrical power supply	208V 60Hz 3Ph, 220V 60Hz 1Ph, 400V 50Hz 3Ph, 400V 50Hz 3Ph
MAX power installed	3.6 kW (208V 60Hz), 3.8 kW (220V 60Hz), 1.8 kW (400V 50Hz)
Maximum current	14 A (208V 60Hz), 17 A (220V 60Hz), 5 A (400V 50Hz)
Dimensions of the sealing bars	510 mm (no.2 side bars)
Packaging cycle (Vacuum 99.9%)	Vacuum = 23 s, Air re-immission = 8 s
Vacuum pump	40 mc/h
Work surface height	889 mm
Machine dimensions (lid open)	773x758x1313 mm
Machine dimensions (lid closed)	773x758x1028 mm
Machine weight (Net/Gross)	180/205 kg
Chamber available dimensions (Tank+lid)	562x518x241 mm

Layout Drawing

