

# MVS52 DV X

**MVS52 DV X: A Dependable and User-Friendly Professional Vacuum Sealer**

Developed in collaboration with renowned chefs, the MVS X chamber vacuum sealer series boasts avant-garde features and advanced technological components, ensuring unparalleled ease of use. This line of vacuum packaging machines is specifically designed to meet the demands of professional packaging, incorporating functionalities tailored to industry requirements.

The models within the series feature a tactile control keypad strategically placed on the front of the body, ensuring a hermetic seal that prevents any risk of liquid infiltration into the board. The control panel allows seamless access to 10 customizable programs through a simple touch interface. A dedicated message on the display prompts users to change the oil when necessary, enhancing the overall maintenance process. Additionally, an internal electronic sensor accurately measures the vacuum achieved in the chamber. These vacuum packaging machines are adaptable to different altitudes, with the capability to calibrate according to atmospheric pressure levels.



## Technical Features

Feature	Specification
Electrical power supply	208V 60Hz 3Ph
MAX power installed	3,6 kW (220V 60Hz 1Ph)
Maximum current	13 A (208V 60Hz)
Dimensions of the sealing bars	530 mm (no. 2 side bars per tank - Total: 4)
Packaging cycle	Vacuum= 22 s Air re-immission= 5 s
Vacuum pump	40 mc/h
Work surface height	893 mm
Machine dimensions (lid open)	1278x784x1344 mm
Machine dimensions (lid closed)	1278x784x985 mm
Machine weight (Net/Gross)	268/300 kg
Available chamber dimensions	399x519x200 mm (2 tanks)

## Layout Drawing

