

# MVS52 DV XP

The MVS52 DV XP is a professional vacuum packaging machine that comes with automatic labelling. The machine allows for the tracking of internal vacuum, and a label can be printed for each packing operation with all the essential information of the processing. The control panel has been renewed and enhanced with new features, making it easy to navigate and program maintenance and assistance interventions. The entire line of vacuum packaging machines XP is CE/ETL/NSF certified, ensuring compliance with industry standards. The MVS52 DV XP is an innovative and revolutionary solution for the food industry, designed to meet the specific needs of professional users, making it an ideal choice for high-capacity applications in the food retail and food processing industries.



## Technical Features

| Feature                         | Specification                                   |
|---------------------------------|---|
| Electrical power supply         | 220V 60Hz 1Ph<br>400V 50Hz 3Ph                  |
| MAX power installed             | 3,6 kW (220V 60Hz 1Ph)<br>3 kW (400V 50Hz 3Ph)  |
| Maximum current                 | 16 A (220V 60Hz 1Ph)<br>7 A (400V 50Hz 3Ph)     |
| Dimensions of the sealing bars  | 530 mm<br>(no. 2 side bars per tank - Total: 4) |
| Packaging cycle                 | Vacuum= 22 s<br>Air re-immission= 5 s           |
| Vacuum pump                     | 40 mc/h   |
| Work surface height             | 893 mm  |
| Machine dimensions (lid open)   | 1278x784x1344 mm                                |
| Machine dimensions (lid closed) | 1278x784x985 mm                                 |
| Machine weight (Net/Gross)      | 268/300 kg                                      |
| Available chamber dimensions    | 399x540x155 mm (2 tanks)                        |